



Plastic formliners MUST be stored at a temperature range of 55° to 85° Fahrenheit. Failure to do so will result in will warrant them both unusable and destroyed. Therefore, AP Thermoforming will NOT assume any liability for



1035 Little Gap Highway Palmerton PA, 18071 610-826-4579 Fax: 610-826-4614

permanent distortion to these plastic formliners and damaged formliners caused from improper storage	ITEM # 30	9065
Customer:	Drawn By:	Date:
Job Name:	Approved By:	Date:
Title:	Scale: None	Tolerance: $\pm 1/16$
	Page: 1	Drawing Number:

	Formliner may require backing provided by customer	This material is the confidential and proprietary property of Architectural Polymers, Inc. ("AP") that you are only permitted to use under license in connection with your business dealings with AP. Unless you and AP agree otherwise in writing, AP grants you a limited license to use these documents/plans, but you may not copy, modify, distribute. or transmit or disclose this material to others without AP's written consent. Copyright 2017 Architectural Polymers, Inc.
Grand and a second s		
61.33.   61.33		
	=	
	1/32	
	9	

Plastic formliners MUST be stored at a temperature range of 55° to 85° Fahrenheit. Failure to do so will result in permanent distortion to these plastic formliners and will warrant them both unusable and destroyed. Therefore, AP Thermoforming will NOT assume any liability for damaged formliners caused from improper storage



1035 Little Gap Highway Palmerton PA, 18071 610-826-4579 Fax: 610-826-4614

Cusi	tomer:
lob	Name:
ľ	
Title	
	#602-S 001 Modular 1/2 Running Bond Assembled

## quired



ITEM #	309065
Drawn By:	Date:
Approved By:	Date:
Scale: None	Tolerance: $\pm 1/16$
Page: 2	Drawing Number: