


Typical Raked Joint Profile



Plastic formliners MUST be stored at a temperature range of 55° to 85° Fahrenheit. Failure to do so will result in permanent distortion to these plastic formliners and will warrant them both unusable and destroyed. Therefore, AP Thermoforming will NOT assume any liability for damaged formliners caused from improper storage

AP THERMOFORMING, LLC

1035 Little Gap Highway Palmerton PA, 18071 610-826-4579 Fax: 610-826-4614

iaiiiageu ii	orininers caused from improper storage		
Customer:]
ob Name:			
		ŀ	
l'itle:	#602-S Modular 1/2 Running Bond (Rake)	•	j

 ITEM # 309504

 Drawn By:
 Date:

 Approved By:
 Date:

 Scale:
 None

 Tolerance:
 ±1/16

 Page:
 1

 Drawing Number:



6'-31/32"

Plastic formliners MUST be stored at a temperature range of 55° to 85° Fahrenheit. Failure to do so will result in permanent distortion to these plastic formliners and will warrant them both unusable and destroyed. Therefore, AP Thermoforming will NOT assume any liability for

AP THERMOFORMING, LLC

1035 Little Gap Highway Palmerton PA, 18071 610-826-4579 Fax: 610-826-4614

or (damaged formliners caused from improper storage	
	Customer:	Drav
		Аррі
	Job Name:	Scale
	Title: #602-S Modular 1/2 Running Bond (Rake) Assembled	Page
	#002-3 Modular 1/2 Running Dond (Rake) Assembled	

ITEM# 309504

wn By: Date: roved By: Date: Tolerance: $\pm 1/16$ None

Drawing Number: