
Formliner may require backing provided by customer with	your business deal	nfidential and proprietary property c alings with AP. Unless you and AP ag , distribute. or transmit or disclose th	ree otherwise in writing, AP gro	ants you a limited license to use	these documents/plans, but you	ⁿ Approval Signature Re
		ł		3'-4¾"		
	·	%" Overlap	1	8"		<u>%" Underlap</u>
	Overlan					
	%" Ot					
				\square		$\Box \Box$
	5					$\Box \Box$
	3'-1 ¹ %"					
	3-1			\leq		
				\square		
				\leq		
	C C			\leq		
	Underlan					
	11%					
			Tunios	N Covo Joint Profil		

Typical Cove Joint Profile



Plastic formliners MUST be stored at a temperature range of 55° to 85° Fahrenheit. Failure to do so will result in permanent distortion to these plastic formliners and will warrant them both unusable and destroyed. Therefore, AP Thermoforming will NOT assume any liability for damaged formliners caused from improper storage



1035 Little Gap Highway Palmerton PA, 18071 610-826-4579 Fax: 610-826-4614

ermanent distortion to these plastic formliners and lamaged formliners caused from improper storage	ITEM # 305782				
Customer:	Drawn By:	Date:			
Job Name:	Approved By:	Date:			
Title:	Scale: None	Tolerance: $\pm 1/16$			
	Page: 1	Drawing Number:			

equired

Formliner may require backing provided by customer	This material is the confidential and proprietary property of Architectural Polymers, Inc. ("AP") that you are only permitted to use under license in connection with your business dealings with AP. Unless you and AP agree otherwise in writing, AP grants you a limited license to use these documents/plans, but you may not copy, modify, distribute. or transmit or disclose this material to others without AP's written consent. Copyright 2017 Architectural Polymers, Inc.	Approval Signature Require
	6'-8 ³ / ₈ "	

	1]
							\square			
							\Box			
=						Z	\square			
31/32										
-9	Z D	\square	\Box	\square	7 2 2	2	Z Z	\square	\square	7 2 2
						Z	\square			
						Z	\square			
						Z				
						Z				
						\square	\Box			

Customer:

Plastic formliners MUST be stored at a temperature range of 55° to 85° Fahrenheit. Failure to do so will result in permanent distortion to these plastic formliners and will warrant them both unusable and destroyed. Therefore, AP Thermoforming will NOT assume any liability for damaged formliners caused from improper storage



1035 Little Gap Highway Palmerton PA, 18071 610-826-4579 Fax: 610-826-4614

Job Name:		
Title:		
	#606-S Modular Stacked Bond Assembled	

uired.

ITEM # 3	305782
Drawn By:	Date:
Approved By:	Date:
 Scale: None	Tolerance: $\pm 1/16$
Page: 2	Drawing Number: