
Formliner may require backing provided by customer

his material is the confidential and proprietary property of Architectural Polymers, Inc. ("AP") that you are only permitted to use under license in connection with your business dealings with AP. Unless you and AP agree otherwise in writing, AP grants you a limited license to use these documents/plans, but you may not copy, modify, distribute. or transmit or disclose this material to others without AP's written consent. Copyright 2017 Architectural Polymers, Inc.

Approval Signature Required

			6'-()3/8"		
	³ / ₈ " Overla	ap	1'-0''	4	3/8"	Underl
Dverlap						
VC						
3%						
(m)						
= = 8						
4'-0 [%] " , 8						
-+						
dr dr						
Underlap						
de						
J						
'						
3%						

Typical Cove Joint Profile



Plastic formliners MUST be stored at a temperature range of 55° to 85° Fahrenheit. Failure to do so will result in permanent distortion to these plastic formliners and will warrant them both unusable and destroyed. Therefore, AP Thermoforming will NOT assume any liability for damaged formliners caused from improper storage



1035 Little Gap Highway Palmerton PA, 18071 610-826-4579 Fax: 610-826-4614

customer.	
Job Name:	
-	
Title:	
	606-S Norman Stacked Bond
	000-5 INOIMAII Stacked Donu



ITEM # 308	3126
Drawn By:	Date:
Approved By:	Date:
 Scale: None	Tolerance: $\pm 1/16$
Page: 1	Drawing Number:

	This material is the confidential and proprietary property of Architectural Polymers, Inc. ("AP") that you are only permitted to use under license in connection	
Formliner may require backing provided by customer	with your business dealings with AP. Unless you and AP agree otherwise in writing, AP grants you a limited license to use these documents/plans, but you may not conv. modify, distribute, or transmit or disclose this material to others without AP's written consent. Convicint 2017 Architectural Polymers, loc	Approval Signature Requ
	may not copy, modify, distribute. or transmit or disclose this material to others without AP's written consent. Copyright 2017 Architectural Polymers, Inc.	rippiovai oigilature reequ

		indy not	. copy, mouly, uistribute	uns material to others w	illioul AF 5 Willen cons	ent. Copyright 2017 Art	.milecturur Polymers, mil.	
	L				12'-	03%"		
	[
Γ					У V	N V		

5~	
~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	
$\hat{\mathbf{O}}$	
-	
$\infty$	

1												
Ť												
						2 Z						
	$\Box \Box$					2 Z						
	$\Box $											
	$\Box $										$\Box$	
	$\Box $											
	$\Box \Box$											
	$\Box $					2 2		Image: A state			A A	
	$\Box \Box$					2				2		
	$\Box \Box$					2				2		
	$\Box \Box$					2				2		
	$\Box \Box$					2				2		
1 🕒												
$\downarrow$												
The st	ored at a ter	morature range	of 55° to 85° Fa	hronhoit Eailure	to do so will re	sult in normanor	t distortion to th	ase plastic form	liners and			

Customer:

Plastic formliners MUST be stored at a temperature range of 55° to 85° Fahrenheit. Failure to do so will result in permanent distortion to these plastic formliners and will warrant them both unusable and destroyed. Therefore, AP Thermoforming will NOT assume any liability for damaged formliners caused from improper storage



1035 Little Gap Highway Palmerton PA, 18071 610-826-4579 Fax: 610-826-4614

ob Name:		-
Litle:		_
	606-S Norman Stacked Bond Assembled	

## quired

ITEM # 308	3126
Drawn By:	Date:
 Approved By:	Date:
Scale: None	Tolerance: $\pm 1/16$
Page: 2	Drawing Number: