

# 75-SERIES RTV LIQUID RUBBER

## Part A

Directions: Use with all 75-Series Part Bs. Before use, read Technical Bulletin and SDS for mixing and handling instructions. Combine proper amounts of A and B in a clean mixing container. Mix well, scraping sides and bottom several times. Pour over a properly prepared mold or model as soon after mixing as possible. Demold after 24-48 hours at room temperature. Close container tightly after use.

CONTENTS:

NET WT.

LOT #



**ARCHITECTURAL POLYMERS®**

1220 Little Gap Road • Palmerton, PA 18071  
www.apformliner.com • 610-824-3322

**KEEP OUT OF REACH OF CHILDREN**

**WARNING: MAY CAUSE ALLERGIC RESPIRATORY AND/OR SKIN REACTION. MAY CAUSE EYE AND SKIN IRRITATION. MAY BE HARMFUL IF SWALLOWED.**

Keep away from heat, sparks and flame. Do not taste or swallow. Use in well ventilated area. Do not breathe vapors which may be produced if product is heated, sprayed or used in a confined area. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

**FIRST AID:** If inhaled, remove to fresh air and get medical attention if symptoms occur. In case of skin contact, wash with soap and plenty of water. In case of eye contact, flush eyes with plenty of water and see a doctor. If swallowed, drink water to dilute, then induce vomiting and see a doctor. Call your local poison control center for more information. In case of spill, absorb spill with inert material, then place in suitable container. Dispose of in accordance with regulations.

DISCLAIMER: The information contained herein is considered accurate. However, no warranty is expressed or implied regarding the accuracy of the data, the results to be obtained by the use thereof, or that any such use will not infringe on any patent. Before using, user shall determine the suitability of the product for the intended use and user assumes all risk and liability whatsoever in connection therewith.

# 75-65 RTV LIQUID RUBBER

## Part B

Directions: Before use, read Technical Bulletin and SDS for mixing and handling instructions. Mix ratio by weight is 1A to 1B. Combine proper amounts of A and B in a clean mixing container. Mix well, scraping sides and bottom repeatedly. Pour over a properly prepared mold or model as soon after mixing as possible. Demold after 24-48 hours at room temperature. Close container tightly after use.

CONTENTS: Polyol Methylene bis (2-chloroaniline)

NET WT.

LOT #



**ARCHITECTURAL POLYMERS®**

1220 Little Gap Road • Palmerton, PA 18071  
www.apformliner.com • 610-824-3322

**KEEP OUT OF REACH OF CHILDREN**

**WARNING: MAY CAUSE EYE AND SKIN IRRITATION. SUSPECT CANCER HAZARD. (CONTAINS MOCA WHICH HAS CAUSED CANCER IN LABORATORY ANIMALS)**

Use in well ventilated area. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

**FIRST AID:** In case of skin contact, wash with soap and plenty of water. In case of eye contact, flush eyes with plenty of water and see a doctor. In case of spill, absorb spill with inert material, then place in suitable container. Dispose of in accordance with regulations.

DISCLAIMER: The information contained herein is considered accurate. However, no warranty is expressed or implied regarding the accuracy of the data, the results to be obtained by the use thereof, or that any such use will not infringe on any patent. Before using, user shall determine the suitability of the product for the intended use and user assumes all risk and liability whatsoever in connection therewith.