Formliner may require backing provided by custome	This material is the confidential and proprietory property of Architectural Polymers, Inc. ("/ with your business dealings with AP. Unless you and AP agree otherwise in writing, AP gro may not copy, modify, distribute, or transmit or disclose this material to others without Ai	AP") that you are only permitted to use under license in connection onts you a limited license to use these documents/plans, but you P's written consent. Copyright 2017 Architectural Polymers, Inc.	Approval Signature Required		
		12'-0"			
<u>'0-'4-</u>					
4					
Touture is only for viewal reference actual touture veries					
Texture is only for visual reference actual texture varies.					
Typical Section					
Typical Section					
We We with the second s					
hamtund					
060 HIPS Formliner					
Plastic formliners MUST be stored at a temperature range of 55° to 85° Fahrenheit. Failure to do so will result in permanent distortion to these plastic formliners and will warrant them both unusable and destroyed. Therefore, AP Thermoforming will NOT assume any liability for damaged formliners caused from improper storage				ITEM # 300017	
1		Customen		Drawn By:	Date:
	1035 Little Gap Highway Palmerton PA, 18071	Job Name:		Approved By:	Date:
	610-826-4579	Tide:		Scale: None	Tolerance: ±3/16
AP THERMOFORMING, LLC	Fax: 610-826-4614	202 Tree Ba	rk	Page: 1	Drawing Number: