AP THERMOFORMING, LLC		Plastic formliners MUST be stored at a temperature range of 55° to 85° Fahrenheit. Failure to do so will result in permanent distortion to these plastic formliners and will warrant them both unusable and destroyed. Therefore, AP Thermoforming will NOT assume any liability for damaged formliners caused from improper storage	%" [9.53mm]Underlap	3'-1 ¹ %6" [957.79mm]	%" [9.53mm]Overlap
Fax: 610-826-4614	1035 Little Gap Highway Palmerton PA, 18071 610-826-4579	inge of 55° to 85° Fahrenheit. Failure to do so wi refore, AP Thermoforming will NOT assume any l			may not copy, modify, distribute, or transmit or disclose this material to of 3'-0%" [923.93mm] 8" [203.20mm] 1 1
± 119 Vertical	Customer: Job Name:	ll result in permanent distortion to these pla iability for damaged formliners caused from			15:00se this material to others without AP's written consent. Copyright 2017 Architectural Polymers, Inc.
Vertical Score Lap and Lock			***Vertical score tex	¹ /4" [6.35m	
	Scale: None Tolerance: $\pm 1/16^{"}$ Page: 1 Drawing Number:	ITEM #	***Vertical score texture not shown for clarity***	$\frac{3}{8}$ " [9.91mm $\frac{1}{32}$ " [0.94m]	vnical Section

Formliner may require backing provided by customer with your business dealings with AP. Unless you and AP agree otherwise in writing, AP grants you a limited license to use these documents/plans, but you Approval Signature Required.

##